

- 94.
- [3] 张明杰, 齐立春, 黄利军, 等. TA15 钛合金挤压薄壁型材拉伸性能及差异性研究 [J]. 钛工业进展, 2020, 37(5): 7-11.
- [4] Boyer R R. An overview on the use of titanium in the aerospace industry [J]. Materials Science and Engineering A, 1996, 213(1/2): 103-114.
- [5] Ramanathan A, Krishnan P K, Muraliraja R. A review on the production of metal matrix composites through stir casting-furnace design, properties, challenges, and research opportunities [J]. Journal of Manufacturing Processes, 2019, 42: 213-245.
- [6] Qi J Q, Sui Y W, Chang Y, et al. Superior ductility in as-cast TiC/near- α Ti composite obtained by three-step heat treatment [J]. Vacuum, 2016, 126: 1-4.
- [7] Adegbajo A O, Olubambi P A, Potgieter J H, et al. Spark plasma sintering of graphitized multi-walled carbon nanotube reinforced Ti6Al4V [J]. Materials & Design, 2017, 128: 119-129.
- [8] Huang L J, Geng L, Wang B, et al. Effects of extrusion and heat treatment on the microstructure and tensile properties of in situ TiB₆/Ti6Al4V composite with a network architecture [J]. Composites Part A: Applied Science and Manufacturing, 2012, 43: 486-491.
- [9] Shirvanimoghaddam K, Hamim S U, Akbari M K, et al. Carbon fiber reinforced metal matrix composites: fabrication processes and properties [J]. Composites Part A: Applied Science and Manufacturing, 2017, 92: 70-96.
- [10] Kondoh K, Threrujirapapong T, Imai H, et al. Characteristics of powder metallurgy pure titanium matrix composite reinforced with multi-wall carbon nanotubes [J]. Composites Science and Technology, 2009, 69(7/8): 1077-1081.
- [11] Azarniya A, Azarniya A, Sovizi S, et al. Physicomechanical properties of spark plasma sintered carbon nanotube-reinforced metal matrix nanocomposites [J]. Progress in Materials Science, 2017, 90: 276-324.
- [12] Zhang F M, Wang J, Liu T F, et al. Enhanced mechanical properties of few-layer graphene reinforced titanium alloy matrix nanocomposites with a network architecture [J]. Materials & Design, 2020, 186: 108330.
- [13] Huang L Q, Wang L H, Qian M, et al. High tensile-strength and ductile titanium matrix composites strengthened by TiB nanowires [J]. Scripta Materialia, 2017, 141: 133-137.
- [14] Hou J B, Chi F H, Chi L D, et al. Effects of the interface and mechanical properties of GNPs/TA15 composites through adding B powders [J]. Journal of Alloys and Compounds, 2021: 162538.
- [15] 程超, 陈志勇, 秦绪山, 等. TA32 钛合金厚板的微观组织, 织构与力学性能 [J]. 金属学报, 2019, 56(2): 193-202.
- [16] 林彰乾, 郑伟, 李浩, 等. 放电等离子烧结 TA15 钛合金及石墨烯增强 TA15 复合材料微观组织与力学性能 [J]. 金属学报, 2021, 57(1): 111-120.
- [17] 何伟, 杜小平, 马红征, 等. TA15 钛合金相变点的测定 [J]. 机械工程与自动化, 2014(4): 104-105.
- [18] 张金赞. 放电等离子烧结 Ti-6Al-4V 的组织与性能研究 [J]. 重型机械, 2017(1): 35-38.

行业动态

天成航材 17 t 真空自耗电弧炉正式投产

2022 年 4 月, 陕西天成航空材料有限公司(以下简称“天成航材”)技改扩建二期项目之一的 17 t 真空自耗电弧炉(VAR 炉)正式投产。该 VAR 炉引进自奥地利 INTECO 公司, 可生产最大直径 1160 mm、最大长度 3700 mm、最大质量 17 t 的钛及钛合金铸锭。现利用该 VAR 炉已成功生产出直径 1080 mm、长度 2850 mm、质量 12 t 的 TA1 纯钛铸锭。经检测, 该铸锭表面质量及化学成分均达到工艺设计要求。

该 VAR 炉的全面投产, 是天成航材熔炼能力的再次提质升级, 将进一步满足高端钛合金研发试制及产能提升的需求, 助力国产钛合金的快速转型升级。

此外, 天成航材技改扩建二期项目中的最后 1 台 10 t VAR 炉也已经进入调试阶段。正式投产后, 天成航材铸锭年产能将达到 10 000 t。

(樊昱茹)